

SHOT OVER

F1



SYSTEM FEATURES

- Quickly and easily interchange multiple cameras and lenses
- Compact size and weight allows affordable transport as freight or excess baggage
- No ITAR or EAR restrictions
- Compatible with most FAA and EASA approved aircraft mounts
- Easily integrated onto a wide variety of mounting platforms
- 6-axis gyro stabilized with look down capability
- Windowless operation for brilliant imagery without reflections
- Fiber optic video data transfer for clean 3GHz imagery
- State of the art electronics and design techniques deliver unshakable stability and ultimate functionality
- Customizable graphics overlay for real time operator feedback
- Auto or Steerable horizon with the most advanced steering capabilities on the market
- Inverted operation using auto-position detectors
- Remote controlled polarized filter rotation, rain deflector and other accessories available

SYSTEM SPECIFICATIONS

STABILIZATION

- 6-axis with no gimbal lock
- High performance non-ITAR sensors
- Distributed Multi-processor closed loop servo control system
- Proprietary gimbal control algorithms

GIMBAL FIELD OF VIEW

- Pan: 360 degrees continuous (via electrical and optical rotary joints)
- Tilt: +45 to -140 degrees
- Roll: +-85 degrees (steerable or auto horizon)
- Max slew rate: 100 deg/sec (with auto drift control)

DATA / COMMUNICATION

- Fiber Optic lines
- CAN Bus
- RS 422 Serial Bus
- Ethernet

WEIGHT

- Turret with max payload less than 55kg (122lbs)
- Operator control unit 2.7kg (6lbs)
- Junction control box 4kg (9lbs)
- External cable set: 2.5kg (5.5lbs)

POWER

- 19-72 VDC
- 20 Amps Max draw (at 19VDC)

ENVIRONMENTAL

- Operating Temperature: -20 to +50 degrees C

OPERATOR CONTROL UNIT

- Lightweight
- Customizable video overlay (Monitor Output)
- Recess for camera remotes such as:
 - Sony RM-B750
 - Arri RCU-4
- Other control layouts available upon request

CAMERA OPTIONS

- Arri Alexa M
- RED Epic
- Sony HDC 2500
- Sony F55
- Canon C500
- Other cameras on request

LENS OPTIONS

- Canon 30-300
- Canon 14.5-60
- Angenieux 15-40
- Angenieux 17-80
- Angenieux HR 25-250
- Fujinon 42x13.5
- Fujinon 42x9.7
- Fujinon 23x7.6
- Fujinon 14x4.5
- Other lenses on request
- Interchangeable filters on request

OPTIONS

- GPS Geo pointing
- Auto tracking
- Remote controlled polarized filter rotation
- Window or rain deflector for environmental protection

Manufacturer reserves the right to change specification to reflect improvements and or changes in technology at any time

16644 Roscoe Blvd.
Van Nuys, CA 91406
USA

133 Glenda Drive
Queenstown, 9300
New Zealand

Shotover.com
O: 530 639 2466
Info@shotover.com